



Hamilton Ready Tex Texture



There are no ASTM or government standards for drywall textures. However, Hamilton Textures are the standard against which all others are measured. Regardless of the desired texture pattern, or the type of spray equipment, Hamilton Textures are clearly and consistently superior.

MADE IN THE USA

Ready Tex Premixed Texture

- **Quick, easy, professional results**
- **Convenient for hopper guns**
- **Great for hand texture applications.**

Hamilton offers a ready-mix texture that eliminates the need for expensive mixing equipment and greatly reduces the time spent mixing. With minimal thinning, Hamilton's Ready Tex is smooth and lump free. Ready Tex is perfect for hand and spray textures applied over gypsum board or interior concrete. Ready Tex is packaged in 3.5-gallon cartons for easy stocking and use.

While achieving the required texture pattern is largely a matter of skill and artistry of the applicator, proper equipment and the correct materials are a must. Hamilton Textures are the correct and preferred materials.

Instructions For Use

- 1. Job Conditions** — Minimum temperature of 50° F to be maintained 24 hours prior to application and until “dry” and stable.
 - 2. Mixing** — Add water to a viscosity that is best suited for desired results.
 - 3. Application** — Ready Tex is designed for spray or hand applications. The desired pattern when spray applied is achieved by varying the thickness of the mix, the orifice of the spray tip, and the volume and pressure of the air supply.
 - 4. Coverage** — Approximately 150 to 300 square feet per box, depending on the type of texture applied.
 - 5. Surface Preparation** — Surfaces to receive texture should be treated to minimize differential in surface porosity. A coat of Hamilton’s Prep Tex is recommended for this purpose. (For further information see the technical data sheet on Prep Tex)
 - 6. Decoration** — While decorative ceiling textures do not require painting, unaggregated (wall) textures are designed to be painted. The painting specification should address the application of a “sealer” and/or “undercoater” to equalize porosity over the finished drywall surface.

For areas to receive gloss finishes and/or subject to severe lighting conditions, the application of Hamilton’s Prep Tex prior to texturing is recommended (See Levels of Gypsum Board Finish). Prep Tex is not a sealer, but a “basecoat” product designed to minimize texture differential.
- Note** — Hamilton drywall textures may also be applied to interior concrete surfaces. Contact your Hamilton representative or our office for further information.

Submittal Approvals

Job Name:

Contractor:

Date: