



# Hot Crete Primer

## LEED Material Data Sheet

Date Prepared: February 5, 2021

**Details of the supplier of the L.E.E.D. data sheet**

|   |  |   |
|---|--|---|
| Hamilton Drywall Products<br>295 N. Pekin Road<br>Woodland, WA, 98674 | Phone number: 1-800-871-4998<br>Fax number: 1-800-871-5007<br>Emergency number: Chemtrec: 1-800-424-9300 | Website: <a href="http://www.hamiltonnw.com">www.hamiltonnw.com</a><br><a href="http://www.hamiltondp.com">www.hamiltondp.com</a> |
|---|--|---|

| Section 1 – Quick Identifier – Common Name (on label) | Packaging             | Product Code  |
|---|-----------------------|---------------|
| Hot Crete Primer                                      | 4.8 gal (18.2 L) pail | 8581930060406 |

| Section 2 – Recycled Content (% by weight) – LEEDS® Recycled Content Credit 4.1: |    |
|--|----|
| Total Recycled Content   | 0% |

**Section 3 – Local/Regional Materials – LEEDS® Local/Regional Materials Credit 5.1**

To determine the distance from the manufacturing facility to the job site, use the suggested Google maps (<https://www.google.com/maps/>) straight-line distance measurement calculator:

Instructions when using Google Maps on a computer web browser (recommended):

- o Search the manufacturing facility address.
- o Right click the red pin and select “Measure distance” from the pop-up menu.
- o Search the job site address, left click on the new red pin.
- o Distance found in white box on bottom of screen (in miles and kilometers).

Instructions when using Google Maps app for Android and iOS:

- o Search the manufacturing facility address.
- o Tap the address or name of the location that is shown at the bottom of the screen and scroll down to select “Measure distance.”
- o Use your finger to slide the map and black targeting circle to the job site location, so the circle is over the site location (zoom-out/in as required).
- o The direct mileage (or kilometers) total is shown at the bottom of the screen.

|                                |   |
|--------------------------------|---|
| Manufacturing Facility Address | • 295 N. Pekin Road, Woodland, WA, 98674, USA |
|--------------------------------|---|

| Section 4 – VOC Content:   |          |
|--|----------|
| VOC content (VOC of material)  | < 10 g/L |
| VOC content for the South Coast Air Quality Management District (SCAQMD) – Regulatory VOC (less water and exempts) | < 25 g/L |

**Section 5 – Other**  
Environmental Product Declaration (EPD) – see website at [www.hamiltonnw.com](http://www.hamiltonnw.com) under Technical Data – LEED Reports section.

The information and data herein are believed to be accurate and have been compiled from sources believed to be reliable and is offered for your consideration. LEED® applicants should use their own subjective determinations for LEED certification purposes. Hamilton Drywall Products will not be liable for claims relating to any party's use of or reliance on information and data contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete or otherwise misleading.