



Setting Compounds

LEED Material Data Sheet

Date Prepared: February 5, 2021

Details of the supplier of the L.E.E.D. data sheet

Hamilton Drywall Products
295 N. Pekin Road
Woodland, WA, 98674

Phone number: 1-800-871-4998
Fax number: 1-800-871-5007
Emergency number: Chemtrec: 1-800-424-9300

Website: www.hamiltonnw.com
www.hamiltondp.com

| Section 1 – Quick Identifier – Common Name (on label) | Packaging | Product Code |
|---|----------------------|--------------|
| Fast Set 20 | 25 lb (11.3 kg) bag | 895900000713 |
| Fast Set 40 | 25 lb (11.3 kg) bag | 895900000720 |
| Fast Set 90 | 25 lb (11.3 kg) bag | 895900000744 |
| Fast Set 5 Lite | 18 lb (8.2 kg) bag | 895900000768 |
| Fast Set 20 Lite | 18 lb (8.2 kg) bag | 895900000775 |
| Fast Set 20 Lite | 18 lb (8.2 kg) bag | 895900000904 |
| Fast Set 40 Lite | 18 lb (8.2 kg) bag | 895900000782 |
| Fast Set 40 Lite | 18 lb (8.2 kg) bag | 895900000904 |
| Fast Set 40 Lite | 20 kg (44.1 lb) bag | 895900000836 |
| Fast Set 90 Lite | 18 lb (8.2 kg) bag | 895900000799 |
| Fast Set 90 Lite | 18 kg (39.7 lb) bag | 895900000843 |
| Fast Set 180 Lite | 18 lb (8.2 kg) bag | 895900000805 |
| Fast Set 180 Lite | 18 kg (39.7 lb) bag | 895900000850 |
| Smooth Set 20 Lite Sand | 18 lb (8.2 kg) bag | 895900000812 |
| Smooth Set 40 Lite Sand | 18 lb (8.2 kg) bag | 895900000904 |
| Smooth Set 90 Lite Sand | 18 lb (8.2 kg) bag | 895900000911 |
| Super Set Lite 20 | 18 lb (8.2 kg) bag | 895900000621 |
| Super Set Lite 40 | 18 lb (8.2 kg) bag | 895900000638 |
| Super Set Lite 60 | 18 lb (8.2 kg) bag | 895900000645 |
| Super Set Lite 90 | 18 lb (8.2 kg) bag | 895900000652 |
| Super Set 20 | 25 lb (11.3 kg) bag | 895900000256 |
| Super Set 40 | 25 lb (11.3 kg) bag | 895900000263 |
| High Density 15 | 25 lb (11.3 kg) bag | 895900000812 |
| High Density 20 | 25 lb (11.3 kg) bag | 895900000676 |
| High Density 40 | 25 lb (11.3 kg) bag | 895900000683 |
| High Density 90 | 25 lb (11.3 kg) bag | 895900000706 |
| Fast Set 5 Lite | 4.5 lb (2 kg) box | 895900000355 |
| Fast Set 20 Lite | 4.5 lb (2 kg) box | 895900000379 |
| Pro-Patch 5 Lite | 8.2 kg (18.1 lb) bag | 000516221807 |
| Pro-Patch 20 Lite | 8.2 kg (18.1 lb) bag | 000516221852 |
| Super Set Lite 20 | 18 lb (8.2 kg) bag | 000516221241 |
| Super Set Lite 40 | 18 lb (8.2 kg) bag | 000516221258 |
| Super Set Lite 60 | 18 lb (8.2 kg) bag | 000516221265 |
| Super Set Lite 90 | 18 lb (8.2 kg) bag | 000516221272 |
| Ultra-Fill | 15 kg (33.1 lb) bag | 895900000591 |
| Ultra-Ceil | 15 kg (33.1 lb) bag | 895900000737 |
| | | |
| | | |

| Section 2 – Recycled Content (% by weight) – LEEDS ® Recycled Content Credit 4.1: | |
|---|----|
| Total Recycled Content | 0% |

Section 3 – Local/Regional Materials – LEEDS ® Local/Regional Materials Credit 5.1

To determine the distance from the manufacturing facility to the job site, use the suggested Google maps (<https://www.google.com/maps/>) straight-line distance measurement calculator:



Setting Compounds LEED Material Data Sheet

Date Prepared: February 5, 2021

Instructions when using Google Maps on a computer web browser (recommended):

- o Search the manufacturing facility address.
- o Right click the red pin and select "Measure distance" from the pop-up menu.
- o Search the job site address, left click on the new red pin.
- o Distance found in white box on bottom of screen (in miles and kilometers).

Instructions when using Google Maps app for Android and iOS:

- o Search the manufacturing facility address.
- o Tap the address or name of the location that is shown at the bottom of the screen and scroll down to select "Measure distance."
- o Use your finger to slide the map and black targeting circle to the job site location, so the circle is over the site location (zoom-out/in as required).
- o The direct mileage (or kilometers) total is shown at the bottom of the screen.

| | |
|--------------------------------|--|
| Manufacturing Facility Address | <ul style="list-style-type: none"> • 295 N. Pekin Road, Woodland, WA, 98674, USA • 341 West Meats Avenue, Orange, CA, 92865, USA |
|--------------------------------|--|

| | |
|--|-------|
| Section 4 – VOC Content: | |
| VOC content (VOC of material) | 0 g/L |
| VOC content for the South Coast Air Quality Management District (SCAQMD) – Regulatory VOC (less water and exempts) | 0 g/L |

| |
|--|
| Section 5 – Other |
| Environmental Product Declaration (EPD) – see website at www.hamiltonnw.com under Technical Data – LEED Reports section. |

The information and data herein are believed to be accurate and have been compiled from sources believed to be reliable and is offered for your consideration. LEED® applicants should use their own subjective determinations for LEED certification purposes. Hamilton Drywall Products will not be liable for claims relating to any party's use of or reliance on information and data contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete or otherwise misleading.