



Acrylic Ad Mix Bonder

LEED Material Data Sheet

Date Prepared: March 9, 2016

Details of the supplier of the L.E.E.D. data sheet

Hamilton Drywall Products
295 N. Pekin Road
Woodland, WA, 98674

Phone number: 1-800-871-4998
Fax number: 1-800-871-5007
Emergency number: Chemtrec: 1-800-424-9300

Website: www.hamiltonnw.com

Common Name (on label / list)	Packaging	Product Code
Acrylic Ad Mix Bonder (2042)	1 gallon (3.8 L) bottle	000516551300

Section 2 – Recycled Content (% by weight) – LEEDS ® Recycled Content Credit 4.1:	Total Recycled Content: 0%
Post Industrial Recycled Content	0%
Post Consumer Recycled Content	0%
Total Recycled Content	0%

Section 3 – Local/Regional Materials – LEEDS ® Local/Regional Materials Credit 5.1	
To determine the distance in statute miles from the manufacturing facility to the project site, use the following suggested direct distance calculator: http://tjpeiffer.com/crowflies.html . Enter the required address information below and click calculate to yield the distance in miles.	
Hamilton Drywall Products – Manufacturing Facility Address – Point A	295 N. Pekin Road, Woodland, WA, 98674, USA
– Point B	Project/Job Site Address

Section 4 – VOC Content:	
VOC content (VOC of material)	< 1 g/L
VOC content for the South Coast Air Quality Management District (SCAQMD) – Regulatory VOC (less water and exempts)	< 5 g/L

The information and data herein are believed to be accurate and have been compiled from sources believed to be reliable, and is offered for your consideration. LEED ® applicants should use their own subjective determinations for LEED certification purposes. Hamilton Drywall Products, LLC., will not be liable for claims relating to any party's use of or reliance on information and data contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete or otherwise misleading.